



An inspection certificate is supplied as standard.
Refer to page U-9 for details.

Dial Indicators


Comparison measuring instruments which ensure high quality, high accuracy and reliability.

SERIES 2 — Standard Type, 0.001 mm & 0.005 mm Graduation


- Standard 0.001 mm and 0.005 mm graduation dial indicators having a bezel with an outside diameter of 57 mm.
- The bezel clamp and lifting lever (optional) can be attached to either the right or left side. These parts can be easily installed and removed without tools.
- Watertight assembly of bezel and crystal as well as the use of an O-ring prevents water or oil penetration.
- The stem and spindle are made of high-strength quench-hardened stainless steel suitable for heavy-duty use.
- A carbide contact point is used.
- A special alloy is used for the sector gears to provide improved wear resistance.
- The indicator uses jeweled bearings, providing excellent indication sensitivity and durability.
- Application of an anti-reflective and hard surface coating improves scale visibility along with scratch and chemical resistance.




2109A-10




Graduation: 0.001 mm, Measuring range: 1 mm
2109A-10
 Shockproof
 Jeweled bearing




Graduation: 0.001 mm, Measuring range: 1 mm
2110A-10
 Double scale spacing
 Shockproof
 Jeweled bearing




Graduation: 0.001 mm, Measuring range: 2 mm
2113A-10
 Shockproof
 Jeweled bearing



Graduation: 0.001 mm, Measuring range: 5 mm
2118A-10
 Jeweled bearing



Graduation: 0.001 mm, Measuring range: 5 mm
2119A-10
 Jeweled bearing



Graduation: 0.005 mm, Measuring range: 5 mm
2124A-10
 Jeweled bearing